



# Hustler X-ONE™

**2** YEAR | **NO** HOUR LIMIT  
LIMITED WARRANTY

OR

**5** YEAR | **500** HOUR  
LIMITED WARRANTY

*\* See your local Hustler dealer for complete warranty details*

## Features and Benefits

- NEW 48, 54, 60 Side Discharge deep decks with VX4™ Technology
- PROVEN separate pumps and motors
- Up to 31 hp
- 11 mph
- 10.4 gallon fuel capacity
- 54, 60 Rear-Discharge decks



**LIMITED**  
**LIFETIME**  
**WARRANTY**  
FRAME & LEADING EDGE OF DECK

*\* Original Purchaser Only*

[hustlerturf.com](http://hustlerturf.com)

**HUSTLER**  
Cutting Grass Not Corners





# X-ONE™ Specifications

## Engines

**Kawasaki FX**  
24 hp

**Kawasaki FX**  
26 hp

**Kawasaki FX**  
31 hp

**Kohler Command**  
25 hp

**Kohler Command**  
27 hp

### More Engine Information:

• [www.kawpower.com](http://www.kawpower.com)

• [www.kohlerengines](http://www.kohlerengines)

### ENGINE

**Starter:** 12-volt

**Ignition:** Electronic

**Charging System:** 12-volt (see engine manufacturer specs)

**Fuel:** Unleaded gasoline (see engine manufacturer specs)

**Fuel Filter:** Replaceable, automotive-type

**Air Cleaner:** Heavy-duty air cleaner to extend the service interval for excessive, dirty applications and improved performance

**Cooling:** Air cooled. Fly-wheel fan

**Governor:** Mechanical

### TRACTION DRIVE SYSTEM

**Type:** Dual hydrostatic. Individual pumps power two direct-drive wheel motors. Hydrostatic system operates on 20W50 motor oil.

**Pumps:** Two variable displacement, axial-piston type. Each pump powers one drive-wheel motor. Hydro-Gear PK 12cc Pump

**Pump Drive:** V-belt drive from engine crankshaft

**Hydraulic Lines:** Stainless-steel, high-pressure lines with Parker Seal-Lok™ O-Ring Face-Seal fittings.

**Final Drive:** Direct-drive high-torque wheel motors. One for each drive wheel. Parker TF0240

**Filter:** Internal

### Ground Speed

**Forward:** Infinitely variable: 0-11 mph

**Reverse:** 0-6 mph

**Steering:** SmoothTrak™ twin-lever steering provides independent control of each drive wheel. Speed, forward, reverse, brake, and turns are all controlled with hand-operated controls

**Turning:** True zero turning radius. Turns within its own length. Counter-rotating, independent drive wheels

### Brakes

**Service:** Hydrostatic dynamic braking

**Parking:** Automotive-style drum brakes. When steering levers are placed in park position, integral park brakes are automatically engaged.

### Tires

**Front:** 13 x 6.5 – 6, rib tread

**Drive:** 48 & 54: 23 x 9.5 – 12, 60: 24 x 12.0 – 12

**Capacities Fuel System:** 10.4 US gal (37.85 l)

### GENERAL INFORMATION

**Safety Features:** Standard foldable ROPS with seat belt. Operator presence system connected to seat, deck clutch and park brake switches. Stabilizer wheels at rear of lawn mower. Side discharge deck with discharge chute and rear discharge deck with deflectors.

**Seat:** Deluxe vinyl seat with armrests. Fore and aft sliding adjustment.

**Construction:** Main frame is 1.5 in x 2.0 in x .188 in square steel tubing. Front caster wheels mounted with sealed ball bearings on each wheel. Front caster forks are .375 in (.95 cm) steel

**Controls:** Hand-operated choke, throttle, ignition switch, electric mower clutch. Integrated parking brakes

**Indicators:** Engine warning light (low oil pressure)

**Cup Holder:** Cup holder molded into the left side fuel tank.

**ROPS:** Certified, 2-post, foldable ROPS with seatbelt.

### DIMENSIONS

**Height:** 53.00 in (133.35 cm) With ROPS folded

71.25 in (172.47 cm) With ROPS up

**W/48" Side-Discharge Deck**

**Length:** 80.8 in (205.23 cm)

**Overall width:** 53.50 in (135.89 cm) w/discharge chute up

**Tire-to-tire width:** 47 in (119.38 cm)

**Weight:** 1200 lbs (544 kg)

**W/54" Side-Discharge Deck**

**Length:** 80.8 in (205.23 cm)

**Overall width:** 59.25 in (150.50 cm) w/discharge chute up

**Tire-to-tire width:** 47 in (129.54 cm)

**Weight:** 1210 lbs (548 kg)

**W/60" Side-Discharge Deck**

**Length:** 83.25 in (211.46 cm)

**Overall width:** 66 in (168 cm) w/discharge chute up

**Tire-to-tire width:** 54 in (137.6 cm)

**Weight:** 1260 lbs (571 kg)

### DECKS

**Side-Discharge:** 48", 54" or 60"

**Rear-Discharge:** 54", 60"

**Type:** Free-floating mower deck using three blades with center blade to the front. Includes 3 deck-mounted rollers to improve flotation in rolling and uneven terrain

**Deck Lift:** Raise and lower deck from driver's seat with simple foot-operated deck height adjustment. Pin for setting height, transport position. Change cutting heights, climbing curbs and trailer more easily.

**Construction:** Welded steel. Solid 1.5 in x .375 (2.55 cm x .95 cm) steel bars reinforce impact areas on trim edges. Commercial style, box section reinforced front edge. Reinforcements welded onto spindle mount areas. High density, rubberized discharge chute.

**Cutting Heights:** Foot-operated deck height adjustment. Pin for setting height, detent for transport position. Height adjustment in .25 in increments from 1.0 in to 5.5 in (3.81 cm

to 13.97 cm)

**Mowing Blades:** Heavy-duty, heat-treated, high-lift steel Fusion™ blades. Fusion blades feature an exclusive electro-fusion technology that creates an ultra-hard layer at the blade's cutting edge, the blade remains sharp and continues to give a clean cut far longer than any blade on the market.

48 in: 16.5 in x 2.5 in x .20 in

54 in: 18.5 in x 2.5 in x .20 in

60 in: 20.5 in x 2.5 in x .20 in

**Blade Tip Speed** (at 3600 RPM engine speed)

Side-Discharge	Rear-Discharge
----------------	----------------

48 in: 18,580 fpm	
-------------------	--

54 in: 18,340 fpm	54 in: 18,580 fpm
-------------------	-------------------

60 in: 18,410 fpm	60 in: 18,410 fpm
-------------------	-------------------

**Deck Drive:** Single V-belt drive from engine with electric clutch to all three spindles. Spring tension idler and large pulleys to extend belt life.

**Spindles:** Ductile iron casting with steel shafts and sealed ball bearings

### Width of Cut

Side-Discharge	Rear-Discharge
----------------	----------------

48 in: 47.25 in	
-----------------	--

54 in: 53.25 in	54 in: 53.10 in
-----------------	-----------------

60 in: 59.25 in	60 in: 59.10 in
-----------------	-----------------

### Trim Capacity

 (left side)

48 in: 0.5 in (1.25 cm) w/9.5 in tire = 0.75 in (1.90 cm)

54 in: 2.5 in (6.5 cm) w/9.5 in tire = 4.75 in (12.06 cm)

60 in: 5.9 in (15 cm) w/12 in tire = 5.75 in (14.60 cm)

### ACCESSORIES

**Flex Forks™:** Shock-absorbing front caster forks for a smooth ride and smoother cut

**Mulch Kit:** Recycles clippings under deck allowing clippings to be cut and recut, then discharged down into the grass. Reduces handling of clippings, improves appearance, and recycles nutrients back to the soil

**Catcher:** Commercial-duty, 12 bushel, rear-mounted, three-bag catcher

**No-Flat Caster Tires:** (Semi Pneumatic)

**Gator™ Blades:** Patented mulching blade design

**Wavy Blades:** Improved performance for mulching

**Other Accessories:** Light Kit, Steering Lever Extension Kit, Optional Rear Anti-Scalp wheel, Stripe Kit, Hitch Kit, Sand Kit, Suspension Kit for seat.

*Specifications subject to change without notice.*