



FASTRAK

SERIES



FASTRAK

AVAILABLE DECK SIZES
48"- 60" 48"- 54" RD



FASTRAK SDX

AVAILABLE DECK SIZES
48"- 60"

FASTRAK



Fabricated Frame for Durability

1.5" x 3.0" steel frame making it one of the toughest and most durable in its class.

Welded Steel Deck

Durable 10 ga. welded fabricated steel.

SmoothTrak™ Steering

Precision control to help trim and maneuver easily around obstacles. You will fully understand SmoothTrak steering when you drive ours and drive theirs.

Serviceable Commercial Grade Transmission

Hydro-Gear® ZT-3200™

Easy Serviceability

Flip-up seat pan and removable floor pan and toolless removable pulley covers makes maintenance easy and simple

Foot Operated Deck Lift

Easily adjust the deck height between 1.5" -4.5" with your foot.

BigBite™ Tires

For smooth ride and enhanced traction.

Premium Seat

High-back seat with suspension to shield the operator from bumps and EVC cushion to take pressure off tail bone and lower back.

Commercial-Grade Kawasaki® FT Engine

With Vortical Air Filtration assists with cleaning debris that extends engine life.

LIMITED WARRANTY

4 YEAR | **750** HOUR



UPGRADES FOUND ON THE FASTRAK SDX

FASTRAK^{SDX}

- ✓ **Extra High-Back Suspension Seat**
Higher backrest and more bolstered back cushion.
- ✓ **Kawasaki® FX Engine**
(Full Commercial Remote Canister Air Cleaner)
- ✓ **Larger Transmissions**
(Hydro-Gear® ZT-3400™)



ACCESSORIES

- ▶ Mulch kit
- ▶ Flex Forks®
- ▶ 2-bag powered bagger (7.2 bushels)
- ▶ Steering lever extension kit
- ▶ Light kit
- ▶ Stripe kit



LIMITED
WARRANTY

4 YEAR | **1000**
YEAR | HOUR

FASTRAK		FASTRAK SDX
ENGINE		
Manufacturer	Kawasaki FT series, KOHLER 7500 EFI	
HP	48", 48" RD, 54", 54" RD deck: 22HP - FT691 54", 60" deck: 27HP - 7500 EFI 60" deck: 24HP - FT730 (Per SAE J1995)	Kawasaki FX series 48", 54" deck: 22HP - FX691 60" deck: 23.5HP - FX730 (Per SAE J1995)
Displacement	48", 48" RD, 54": 726cc FT691 54", 60": 747cc 7500 EFI 60": 726cc FT730	726cc
Cooling	Air cooled	
Engine Warranty	3 year	
DRIVE SYSTEM		
Type	Dual hydrostatic	
Transmission	Hydro-Gear® ZT-3200™	Hydro-Gear® ZT-3400™
Speed	Up to 8 mph	Up to 9 mph
Parking Brakes	Patented automatic	
DECKS		
Cutting Width	Side discharge: 48", 54", 60" Rear-discharge: 48", 54"	Side discharge: 48", 54", 60"
Cutting Heights	1.5" - 4.5"	
Deck Lift	Foot operated	
Depth	5"	
Blades	3	
Blade Length	48", 48"RD: 16.50" 54", 54"RD : 18.50" 60" deck: 20.50"	48" deck: 16.50" 54" deck: 18.50" 60" deck: 20.50"
Blade Tip Speed	48", 48"RD: 18,600 54", 54"RD: 18,900 60": 18,400	48": 18,600 54": 18,900 60": 18,400
Spindles	Aluminum with 1.0" shafts and sealed ball bearings	
Drive	Electric PTO clutch	
Construction	Fabricated 10 ga.	
Spindle Mounts	Reinforced 11 ga.	
Impact/Trim Areas	11ga. formed channel with rolled edge	
CONSTRUCTION		
Frame	1.5" x 3" steel tubing	
Front Axle	Fabricated with sealed ball bearings	
Front Caster Wheels	Heavy duty ball bearings, greasable	
Front Caster Forks	Fabricated 3/8" steel	
GENERAL		
Seat	High-back suspension seat	Extra High-back suspension seat
Fuel Capacity	5 gallons	
Cupholder	Yes	
Front Tire	48", 48" RD: 13 x 5 - 6 54", 54"RD, 60": 13 x 6.5 - 6	48": 13 x 5 - 6 54", 60": 13 x 6.5 - 6
Drive Tire	48", 48" RD: 23 x 9.5 - 10 BigBite™ 54", 54"RD, 60": 23 x 11 - 10 BigBite™	48": 23 x 9.5 - 10 BigBite™ 54", 60": 23 x 11 - 10 BigBite™
DIMENSIONS		
Weight	48": 835 lbs 48" RD: 840 lbs 54": 845 lbs 54" RD: 860 lbs 60": 865 lbs	48": 862 lbs 54": 891 lbs 60": 916 lbs
Height	48.9" 68.7 w/ ROPS up	
Length	48": 73.6" 54": 74.42" 60": 75.92"	
Width w/Chute	48": 49.1" 48" RD: 48.85" 54": 55.1" 54" RD: 54.85" 60": 61.1"	48": 49.1" 54": 55.1" 60": 61.1"
Tire Width	48": 47" 54" & 60": 52"	
Trim Side	48": 1" 54": 3" 60": 6"	
PRODUCTIVITY*		
Acres Per Hour	48" deck: 3.10, 54" deck: 3.48, 60" deck: 3.88	48" deck: 3.49, 54" deck: 3.93, 60" deck: 4.36

* Number based on 80% efficiency. This rating is to account for actual mowing conditions including overlapping, turning and terrain.

** Specifications are subject to change without notice.